

Series
MR - MA - ML
VM - MR

Manifolds - fittings
and hydraulic oil up to
4.000 bar







PRODUCT
PAGE





For quick and safe connection of
the hydraulic circuits

CUSTOM VALVES ON REQUEST





















- Used to connect multiple lines to one inlet.
- Built with radial or linear outlet. The linear models are supplied with a pressure gauge installation hole.
- Available in 11 standard models and in custom versions for high pressure jobs.
- From 700 to 4.000 bar




	MODEL	NUMBER OF USES	MAX WORKING PRESSURE (bar)	DIMENSIONS (mm)									
				A	B	C	D	E	F	G	H		
	MR - 3V	3	700	70	26	3/8" NPT							
	MR - 5V	5		70	26	3/8" NPT							
	MR - 11V	11		148	35	3/8" NPT							
	MR - 17V	17		230	35	3/8" NPT							
	ML - 5	5	700	200	45	50	3/8" NPT	G 1/2"	186	31	6,5		
	ML - 7	7		300	45	50	3/8" NPT	G 1/2"	286	31	6,5		
	ML - 9	9		400	45	50	3/8" NPT	G 1/2"	386	31	6,5		
	ML - 11	11		500	45	50	3/8" NPT	G 1/2"	486	31	6,5		

	MODEL	NUMBER OF USES	MAX WORKING PRESSURE (bar)	DIMENSIONS (mm)	
	VM5A/2	3	700		
	VM5A/4	5	700		

AUXILIARY COMPONENTS AND VALVES

	MODEL	NUMBER OF USES	MAX WORKING PRESSURE (bar)	DIMENSIONS (mm)		
	VM5A/1600	2	1600			
	VM5A/2000	2	2000			
	VM5A/4000	2	4000			

	MODEL	NUMBER OF USES	MAX WORKING PRESSURE (bar)	DIMENSIONS (mm)	
	MR3V/1500	3	1500	MR3V/1500 	MR3V/2500 
	MR3V/2500	3	2500		
	MR5V/1500	5	1500	MR5V/1500 	MR5V/2500 
	MR5V/2500	5	2500		

TYPE	MODEL	MAX WORKING PRESSURE (bar)	DIMENSIONS (mm)				
			A	B	C	D	
NIPPLE	0925613265	2000	45	CH 17	G"1/4 - 120°	G"1/4 - 120°	
NIPPLE	09299199501611	3000	48,5	CH 21	G"1/4 - 120°	3/4" - 16 UNF	
NIPPLE	0922225257	3000	48	CH 22	M16x1,5	3/4" - 16 UNF	
NIPPLE	0922225482	3000	42	CH 22	G"1/4 - 60°	3/4" - 16 UNF	
NIPPLE	0922225016	4000	40	CH 19	M16x1,5	9/16" - 18 UNF (1/4" HP)	
REDUCTION	0929112241	2500	45	CH 27	G"1/4" - 120° F	3/4"-16 UNF M	
PLUG	0925614601	2000	30	CH 17	-	G"1/4 - 120°	
	0922225585	3000	30	CH 22	-	3/4" - 16 UNF	
	0922221364	4000	26	CH 17	-	9/16" - 18 UNF (1/4" HP)	

TYPE	MODEL AND DIMENSIONS	
	G-241	GF-242
ELBOW		
T-FITTING - CROSS FITTING		

TYPE	MODEL	DIMENSIONS (mm)				
		A	B	C	D	
REDUCTION	R-313	40	CH 27	1/4" NPT	3/8" NPT	
	R-314	40	CH 27	3/8" NPT	1/4" NPT	
	R-316	45	CH 32	G 1/2"	1/4" NPT	
	R-352	45	CH 32	G 1/2"	3/8" NPT	
HEX COUPLING	ME-349	37	CH 27	3/8" NPT	3/8" NPT	
	ME-357	37	CH 27	1/4" NPT	3/8" NPT	
NIPPLE	N-341	39	CH 17	1/4" NPT	1/4" NPT	
	N-343	41	CH 19	1/4" NPT	3/8" NPT	
	N-344	41	CH 19	3/8" NPT	3/8" NPT	
LONG NIPPLE	NL-345	55	3/8" NPT	-	-	
	NL-346	80	3/8" NPT	-	-	
	NL-347	150	3/8" NPT	-	-	

	MODEL	LITRES
	OIL - 1	1
OIL - 5	5	
OIL - 10	10	
BIO-OIL-1	1	
BIO-OIL-5	5	
BIO-OIL-10	10	

MINERAL HIDRAULIC OIL ISO VG 32
Available different oil for custom applications.

BIO OIL - Eco-friendly oil
Eco-friendly oil. High-performance, fully synthetic, biodegradable, non-toxic hydraulic fluid, saturated esters made.

